


-  **IP67**
-  **Class III**
-  **Incasso a parete, pavimento**
Wall, floor recessed
-  **Carrabile 2000 kg**
Drive over up to 2000 kg
-  **Cavo in neoprene 100 cm**
100 cm neoprene cable
-  **Installazione con controcassa obbligatoria**
Recessed box needed
-  **Collegare in serie 350mA o 500mA**
Connect in series at 350mA or 500mA
-  **300 gr**



ASTRO 80

	1W 350mA	2W 500mA	3W 350mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	100lm	150lm	300lm		
 15° Lens			7A0858._ _	 3 Grigio - Gray	 Y 2700K
 30° Lens			760858._ _	 4 Nero - Black	 6 3000K
 60° Lens			750858._ _	 6 AISI 316L Acciaio inox Stainless Steel	 9 4000K
 Vetro satinato Frosted glass	710857._ _	710796._ _			 1 5000K
 Lente ellittica Elliptical lens			770858._ _		

LED COLOUR
FINISH

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

ACCESSORI
ACCESSORIES

350mA CC20-F-350-N
500mA CC20-F-500-N

pag. 190
pag. 192



Controcassa
Recessed box
A00247.30

 Ø 74 mm



Micro connettore
stagno
Micro watertight
connector
A00357.40