

TONO i TONO Qd TONO iR

PRECISIONE E DEFINIZIONE ANCHE ALL'ESTERNO

Questo incasso per esterni è disponibile sia in versione fissa – Tono i – che orientabile – Tono iR. In entrambi i casi si tratta di apparecchi caratterizzati da un volume minimo e che, grazie alla controcassa, assicurano una protezione IP67. L'ottica arretrata assicura un efficace antiabbagliamento. Le due versioni sono disponibili con 3 diverse ottiche e 2 potenze, per garantire la massima flessibilità nella scelta della luce più adatta. Nella versione orientabile l'apparecchio è provvisto di snodo sferico in grado di renderlo omnidirezionale.

PRECISION AND DEFINITION FOR OUTDOOR LOCATIONS

Recessed fixture for outdoor use available in both fixed – Tono i – and adjustable – Tono iR – versions. Both products are characterized by their small dimensions and a housing which guarantees the IP67 rate.

The recessed optic ensures an efficient low glare effect. Both versions are also available with 3 different optics and 2 wattages, in order to guarantee the maximum flexibility in choosing the most suitable light.

OTTICA ARRETRATA

RECESSED OPTIC

ULTRAPIATTO

EXTRA THIN

CON SFERA
ORIENTABILE
A 360°
(TONO iR)

360°
ADJUSTABLE
BALL JOINT
(TONO iR)

GRADO DI PROTEZIONE IP67

PROTECTION RATE IP67

FASCIO 3°

3° BEAM ANGLE



TONO i




TONO Qd



TONO iR

- IP67
- Class III
- Incasso a parete, pavimento
Wall, floor recessed
- Carrabile 2000 kg
Drive over up to 2000 kg
- Collegare in serie 500mA o 900mA
Connect in series at 500mA or 900mA
- 280 gr




TONO i IP67

	3W 900mA	6W 500mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	200lm	450lm		
 3° Lens	7T3630._ _		 3 Grigio - Gray  4 Nero - Black  6 AISI 316L Acciaio inox Stainless Steel	 Y 2700K
 10° Lens	733629._ _			 6 3000K
 30° Lens	763629._ _			 9 4000K  1 5000K
			LED COLOUR	
			FINISH	


TONO i IP67

CON NIDO D'APE WITH HEX LOUVER		3W 900mA	6W 500mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K		200lm	450lm		
 3° Lens	7T3632._ _		 3 Grigio - Gray	 Y 2700K	
 10° Lens	733631._ _		 4 Nero - Black	 6 3000K	
 30° Lens	763631._ _		 6 AISI 316L Acciaio inox Stainless Steel	 9 4000K  1 5000K	
			LED COLOUR		
			FINISH		


TONO i



TONO i



TONO i



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

500mA CC20-F-500-N
900mA CC20-F-900-N


page 168
page 171



Controcassa
Recessed box
A00489.40
page 183

Ø 55 mm

- IP67
- Class III
- Incasso a parete, pavimento
Wall, floor recessed
- Carrabile 2000 kg
Drive over up to 2000 kg
- Collegare in serie 500mA o 900mA
Connect in series at 500mA or 900mA
- 320 gr




TONO Qd IP67

	3W 900mA	6W 500mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	200lm	450lm		
 3° Lens	7T3688._ _		 3 Grigio - Gray	 Y 2700K
 10° Lens	733687._ _		 4 Nero - Black	 6 3000K
 30° Lens	763687._ _		 6 AISI 316L	 9 4000K
			Acciaio inox Stainless Steel	
			LED COLOUR	
			FINISH	


TONO Qd IP67

CON NIDO D'APE WITH HEX LOUVER		3W 900mA	6W 500mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K		200lm	450lm		
 3° Lens	7T3690._ _			 3 Grigio - Gray	 Y 2700K
 10° Lens	733689._ _			 4 Nero - Black	 6 3000K
 30° Lens	763689._ _			 6 AISI 316L Acciaio inox Stainless Steel	 9 4000K  1 5000K
				LED COLOUR	
				FINISH	


TONO Qd



TONO Qd



TONO Qd



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

500mA CC20-F-500-N
900mA CC20-F-900-N

page 168
page 171



Controcassa
Recessed box
A00489.40
page 183

Ø 55 mm